

BlackShield



Nitrile Examination Gloves / Gants D'examen en Nitrile **NBL50**



Application

- Food Handling
- Agriculture
- Industrial
- Cleaning & Janitorial
- Printing & Painting
- Medical & Healthcare
- Household

Technical Specification

Length (mm)	240 mm (min)		
Thickness (mm)	Cuff	Palm	Finger
	0.05 mm (min)	0.09 mm (min)	0.11 mm (min)
Force at break(N)	Unaged		Aged (22hr, 100c)
Tensile Strength at break	14 MPa (min)		14 MPa (min)
Elongation at break	500 %		500 %

Sizes **Width** **Weight**
(+/- 10 mm) (+/- 0.3 gm)

S	80 mm	4.5 gm
M	95 mm	5.0 gm
L	110 mm	5.5 gm
XL	120 mm	6.0 gm

Features

- Colour **Black**
- AQL 1.5
- Ambidextrous
- Non-Sterile
- Beaded Cuff
- Latex Free, No Natural Rubber Protein
- Powder Free, No Cornstarch
- Micro Textured Surface For Secure Grip
- Enhanced Comfort
- Super Soft and Fatigue Free
- Accelerator Free
- Type I and IV Allergy Free

Certification



- ASTM : D 6319- 10 (2015)
- EN 455 : Part 1,2,3,4
- EU CE Regulation 2016/ 425
- EN 420 : 2003 + A1 2009
- EN ISO 374-1: 2016
- EN 374-2: 2014
- EN 374-4: 2013
- EN ISO 374-5: 2016
- EN 16523: 2015
- EU 10/2011
- EN 455:1,2,3,4

Packaging

100 GLOVES x **10 BOXES** = **1000 GLOVES/CASE**
GANTS x **BOÎTES** = **1000 GANTS / CAS**